







f

Massive And Smart

The new V-Strom 250/ABS is equally at home in city traffic as it is on the open road when touring. Featuring a comfortable riding position and enabling riders to firmly reach the ground with their feet, this new model also delivers plenty of power and easy to control low- to mid-range torque.



Pearl Nebular Black / Solid Dazzling Cool Yellow (BJE) Photo: DL250A

SPECIFICATIONS	V-Strom 250/ABS

Overall length 2,150 mm (84.6 in)		
Overall width	790 mm (31.1 in)	
Overall height	1,295 mm (51.0 in)	
Wheelbase	1,255 mm (51.0 m)	
Ground clearance	1,425 mm (50.1 m)	
Seat height Curb mass	800 mm (31.5 in)	
	188 kg (414 lbs)	
Engine type	4-stroke, 2-cylinder, liquid-cooled, SOHC	
Bore × Stroke	53.5 mm x 55.2 mm (2.1 in x 2.2 in)	
Engine displacement	248 cm3 (15.1 cu. in)	
Compression ratio	11.5 : 1	
Fuel system	Fuel injection	
Starter system	Electric	
Lubrication system	Wet sump	
Transmission	6-speed constant mesh	
Primary reduction	ratio 3.238 (68/21)	
Final reduction	ratio 3.357 (47/14)	
Suspension		
Front	Telescopic, coil spring, oil damped	
Rear	Swingarm type, coil spring, oil damped	
Rake / Trail	25.2° / 100 mm (3.9 in)	
Brake		
Front	Disc brake	
Rear	Disc brake	
Tire		
Front	110/80-17M/C 57H tubeless	
Rear	140/70-17M/C 66H tubeless	
Ignition system	Electronic ignition (Transistorized)	
Fuel tank capacity	17.3 L (4.6/3.8 US/Imp gal)	
Oil capacity (Overhaul)	2.4 L (2.5/2.1 US/Imp qt)	



Bell Village 405 1000 Flacq 405 1088 Forbach 405 1100 Rodrigues 831 0592



Pearl Nebular Black (YAY) Photo: DL250A



Metallic Triton Blue No.2 (QHV) Photo: DL250A

Pearl Nebular Black / Metallic Hightech Silver (BY6) Photo: DL250A